

# Dimensioni delle guarnizioni FLESSO

DN	Pn	Ø <sub>+</sub> mm	Ø <sub>↓</sub> mm	→← mm	peso g
25	10/40	35	70	3	28
32	10/40	43	82	3	30
40	10/40	49	92	3	36
50	10/40	61	107	4	41
65	10/40	77	127	4	58
80	10/40	90	142	4	68
100	10/16	115	162	5	87
100	25/40	115	168	5	95
125	10/16	141	192	5	116
125	25/40	141	192	5	120
150	10/16	169	218	5	136
150	25/40	169	225	5	136
200	10/16	220	273	6	200
200	25	220	285	6	228
200	40	220	292	6	234
250	10/16	273	328	6	260
250	25	273	340	6	260
250	40	273	352	6	270
300	10	325	378	6	290
300	16	325	385	6	295
300	25	325	402	6	295
300	40	325	417	6	305
350	10/16	368	438	7	584
350	25	368	457	7	590

DN	Pn	Ø <sub>+</sub> mm	Ø <sub>↓</sub> mm	→← mm	peso g
400	10	407	490	7	620
400	16	407	496	7	620
400	25	407	514	7	635
400	40	407	546	7	650
450	10/16	470	540	7	700
500	10	520	595	7	900
500	16	520	618	7	935
500	25/40	520	625	7	935
600	10	620	695	7	930
600	16	620	735	7	950
600	25	620	731	7	1000
700	10/16	720	810	8	1115
700	25	720	833	8	1150
800	10/16	820	915	8	1620
800	25	820	942	8	1650
900	10/16	915	1017	8	1820
900	25	915	1042	8	1870
1000	10/16	1016	1124	8	2100
1000	25	1016	1154	8	2150
1200	10/16	1220	1341	8	2400
1400	10	1420	1548	8	4500
1600	10	1620	1772	8	6000
1800	10	1820	1972	8	6600
2000	10	2020	2182	8	7000